

# MILLTEK

|             |          |
|-------------|----------|
| SYSTEM NO.  | SSXH0321 |
| DESCRIPTION | Cat-back |
| NOTES       |          |

## PARTS REQUIRED

| PART NO.        | DESCRIPTION                               | QUANTITY | IN PACKAGE |
|-----------------|-------------------------------------------|----------|------------|
| <b>F7098</b>    | <b>Heatshield for Rear Silencer</b>       | <b>1</b> |            |
| <b>MSH0133</b>  | <b>Front Silencer</b>                     | <b>1</b> |            |
| CHC79SS         | 79mm Band Clamp - 304 S/S                 | 1        |            |
| <b>MSH0134</b>  | <b>Centre Silencer</b>                    | <b>1</b> |            |
| CHC79SS         | 79mm Band Clamp - 304 S/S                 | 1        |            |
| <b>MSH0135</b>  | <b>Rear Connecting Pipe</b>               | <b>1</b> |            |
| CHC79SS         | 79mm Band Clamp - 304 S/S                 | 1        |            |
| <b>MSH0155</b>  | <b>Front Connecting Pipe with Flex</b>    | <b>1</b> |            |
| F3116           | Gasket 1.5mm                              | 1        |            |
| <b>MSH0157</b>  | <b>Valved Outlet Pipe</b>                 | <b>1</b> |            |
| CHC79SS         | 79mm Band Clamp - 304 S/S                 | 1        |            |
| F3160           | Wire Formed Spring Assembly               | 1        |            |
| M5FLGNUT        | M5 X 0.8 Nylon Coat Flange Nut            | 3        |            |
| <b>MSH0163</b>  | <b>Rear Silencer (ECE Version)</b>        | <b>1</b> |            |
| CHC79SS         | 79mm Band Clamp - 304 S/S                 | 1        |            |
| <b>MSTIP251</b> | <b>4.5" Tailpipe - Cerakote Black x 3</b> | <b>3</b> |            |
| CHC66.5SS       | 66.5mm Band Clamp-304 S/Steel             | 3        |            |

## TECHNICAL INFORMATION

|       |                                                                                                                                                                                 |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOTES | Uses OE actuator, make sure Milltek Valve is in the CLOSED POSITION before installing the actuator. Once the vehicle is turned on the valve will align and operate as standard. |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|